



Intertape PG777 Technical Datasheet



Product Description

PRODUCT APPLICATION Paint masking, either OEM or repair. Allows clean removal from aluminium, primed aluminium, and painted aluminium surfaces even when cycled three or more times.

GOVERNMENT COMPLIANCE BAC 5034-4

STORAGE RECOMMENDATION Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

SHELF LIFE When stored under recommended conditions, converted rolls have an expected shelf life of up to one (1) year from the date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within six (6) months of date of shipment.

NOMINAL VALUES The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing – Smooth Crepe Paper

Adhesive – Natural Rubber / Resin

Adhesion to Steel (oz/in of width) – 30 (8.2 N/25mm)

Tensile Strength (lbs/in of width) – 30 (131.3 N/25mm)

Total Thickness (mils) – 7.7 (0.196mm)

Quick Stick (oz/in of width – 17 (4.7 N/25mm)

SKU: PG777

Fraser's Aerospace, 1 St James Road, Brentwood, Essex, CM14 4LH

Tel: +4420 8597 8781 Email: contact@frasersaerospace.com Web: www.frasersaerospace.com