



Strutwipes (6x6-SW-756) Technical Datasheet



Product Description

StrutWipe 756 is an excellent choice for cleaning chrome piston cylinders and struts. The wipe is pre-saturated with top of the line hydraulic fluid: MIL-PRF-5606. Protect your personnel from hazardous hydraulic fluid until use with our three-layer lamination foil packaging that eliminates vapor exposure emitted by hydraulic fluid. Always wear appropriate personal protective equipment when working with hazardous material.

Our hydraulic presaturated strut wipes are made of 100% cotton cloth woven and finished without starch, binders, or any foreign substances. The cloth finish gives this wipe a softer and better dirt-trapping capacity. This wipe is pre-soaked with hydraulic fluid MIL-PRF-5606 and has incredible retention to maximize fluid to cloth ratio.

Commodity Code: 3405900000

SKU: FA-6x6-SW-756

NATO stock number 7930016856964

Features

Wiping material:

- Shall meet AMS3819 specifications.
- ISO Class 5 (Class 100) and above cleanroom applications.
- Shall be 100% recyclable/biodegradable cotton.
- Shall be low lint, no fraying, and high strength.
- Shall be 100% natural fibers to ensure entrapment of particles down to 5 microns.
- Shall have maximum absorbance.
- Shall be nonabrasive texture that provides superior contaminant removal.
- Shall be static free.

Available in the following sizes: 4inX4in (16 in²), 6inX6in (36 in²), and 9inX9in (81 in²) (Cotton is a natural fabric and will distort during wipe manufacturing process. All dimensions are \pm 0.25 inches).

Hydraulic fluid MIL-PRF-5606:

- Shall meet all requirements and is qualified under MIL-SPEC: MIL-PRF-5606.
- Shall have a wide operating temperature range -65 to 275°F.
- Shall have excellent oxidation and corrosion inhibitors.

Hydraulic fluid MIL-PRF-83282:

- Shall meet all requirements and is qualified under MIL-SPEC: MIL-PRF-83282 Am 1, NATO Code Number H-537.
- Shall have a wide operating temperature range -40 to 401°F.
- Shall have excellent oxidation and corrosion inhibitors.

StrutWipe 756 is an excellent choice for cleaning chrome piston cylinders and struts. The wipe is pre-saturated with top of the line hydraulic fluid: MIL-PRF-5606. Protect your personnel from hazardous hydraulic fluid until use with our three-layer lamination foil packaging that eliminates vapor exposure emitted by hydraulic fluid. Always wear appropriate personal protective equipment when working with hazardous material.

Our hydraulic presaturated wipes are made of 100% cotton cloth woven and finished without starch, binders, or any foreign substances. The cloth finish gives this wipe a softer and better dirt-trapping capacity. This wipe is pre-soaked with hydraulic fluid MIL-PRF-5606 and has incredible retention to maximize fluid to cloth ratio.

Frasers Aerospace, 1 St James Road, Brentwood, Essex, CM14 4LH

Tel: +4420 8597 8781 Email:contact@frasersaerospace.com Web:www.frasersaerospace.com