Blue Dolphin Stucco Masking Tape
Technical Datasheet



Product Description

48mm width. Length available 50m

Blue masking tape for masking paint during metal polishing.

Thickness 115 microns Adhesion to Stainless Steel 180 deg N/2,5 cm Thickness 135 Micron MD tensile strength N/A MD elongation at break N/A Service Temeperature Range -10 to +60 deg C
Commodity Code: 3919100000

SKU: FA-MTPER#5151

Product Description
48mm width. Length available 50m
Blue masking tape for masking paint during metal polishing.
Thickness 115 microns Adhesion to Stainless Steel 180 deg N/2,5 cm Thickness 135 Micron MD tensile strength N/A MD elongation at break N/A Service Temeperature Range -10 to +60 deg C

ADVANTAGES AND BENEFITS
> Serrated edge for easy tear
> Smooth surfaces
> Vinyl, glass, plastic, aluminum
> 30 days clean & easy removal
> UV resistant

TYPICAL APPLICATIONS
> Painted walls & trims
> Lacquered / Varnished woodwork
> Glass, plastic , metal

CONSTRUCTION
Overall Grade: Outside grade
Backing: LDPE
Adhesive: Rubber based, transparent adhesive

STANDARD SIZE
Width(s): 48mm / 2?
Length(s): 50m / 60yd
Contact Frasers at Contact@FrasersAerospace.com for other available sizes.

STORAGE & USAGE CONDITIONS
Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

Frasers Aerospace, 1 St James Road, Brentwood, Essex, CM14 4LH

Tel: +4420 8597 8781 Email:contact@frasersaerospace.com Web:www.frasersaerospace.com