



## Blue Dolphin Stucco Masking Tape Technical Datasheet



---

### Product Description

48mm width. Length available 50m

Blue masking tape for masking paint during metal polishing.

Thickness 115 microns Adhesion to Stainless Steel 180 deg N/2,5 cm Thickness 135 Micron MD tensile strength N/A MD elongation at break N/A Service Temperature Range -10 to +60 deg C

**Commodity Code:** 3919100000

**SKU:** FA-MTPER#5151

### Product Description

48mm width. Length available 50m

Blue masking tape for masking paint during metal polishing.

Thickness 115 microns Adhesion to Stainless Steel 180 deg N/2,5 cm Thickness 135 Micron MD tensile strength N/A MD elongation at break N/A Service Temperature Range -10 to +60 deg C

### ADVANTAGES AND BENEFITS

- > Serrated edge for easy tear
- > Smooth surfaces
- > Vinyl, glass, plastic, aluminum
- > 30 days clean & easy removal
- > UV resistant

### TYPICAL APPLICATIONS

- > Painted walls & trims
- > Lacquered / Varnished woodwork
- > Glass, plastic, metal

### CONSTRUCTION

Overall Grade: Outside grade

Backing: LDPE

Adhesive: Rubber based, transparent adhesive

### STANDARD SIZE

Width(s): 48mm / 2"

Length(s): 50m / 60yd

Contact Frasers at [Contact@FrasersAerospace.com](mailto:Contact@FrasersAerospace.com) for other available sizes.

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

---

Frasers Aerospace, 1 St James Road, Brentwood, Essex, CM14 4LH

Tel: +4420 8597 8781 Email: [contact@frasersaerospace.com](mailto:contact@frasersaerospace.com) Web: [www.frasersaerospace.com](http://www.frasersaerospace.com)