



Nuvite Chemical NuPol Heavy Duty Dry Wash (5USG/19L) Technical Datasheet



Product Description

Nuvite's NuPol (5 USG) is the heavy-duty 'Drywash' cleaner and finish restorer for those really tough situations, such as baked-on carbon exhaust trails, surface staining, dull, dirt-catching and/or oxidised paint – anywhere in need of some serious cleaning muscle!

NuPol is easy to use – just wipe or mop on with spun cotton scrub pad, agitate to a thin layer and let it dry! When you wipe off the dry haze you will see a clean, shiny and U/V protected painted surface! No water, power tools to set up or mess – you can use it anywhere, including in hangars and on ramps. Nuvite's NuPol can beat the toughest paint appearance problems, and when used with other Nuvite paint care products, gives you the easiest and best paint care system at the same time!

Directions For Use.

For Normal or Lightly Soiled Surface Conditions: Apply NuPol "as is" by hand with a soft wiping cloth, applicator pad/mop or working quickly and lightly with slow speed orbital buffer to small areas at a time. Agitate area evenly with wet material. Allow to fully dry (usually no more than 5-10 minutes even in the highest humidity conditions). Remove by polishing off with clean mop head or dry wiping cloth to reveal shine.

For Heavily Soiled Surface Conditions: For the heavy grease, oil, and hydraulic oil build-ups, it is sometimes helpful that the area be wiped down or degreased with Nuvite CitriCut or SS-93 degreasing cleaners prior to the use of NuPol to allow the product to work without serious contamination, then proceed as above.

OEM & Airline Approvals:

Embraer, Gulfstream, Fedex

Note: For 55G (209L) drums, please [click here to contact us](#).

Note: For Safety Data Sheets in languages other than English, please click here to contact us.

Commodity Code: 3405300000

SKU: FA-PC-2205-5USG

Approvals:

- Boeing D6-17487
- AMS 1650
- AMS 1530
- AMS 1531
- AMS 1532
- Douglas CSD #1

Features

- Heavy-duty 'drywash' cleaning
- Restores shine and colour on oxidized paint on all vehicles
- Easy "wipe on, let dry, wipe off" application procedure.

- Safe to all paints (not for clear-coats)
- Restores a beautiful gloss appearance with an effective UV protectant coating on both painted and metal surfaces
- Easy application in all climates
- Preserves and protects the substrate from further oxidation and intensifies colour on oxidised paint surfaces
- Offers superior cleaning results and protection with fewer man-hours

Product Description.

Nuvite's NuPol is the heavy-duty 'Drywash' cleaner and finish restorer for those really tough situations, such as baked-on carbon exhaust trails, surface staining, dull, dirt-catching and/or oxidised paint – anywhere in need of some serious cleaning muscle! NuPol is easy to use – just wipe or mop on with spun cotton scrub pad, agitate to a thin layer and let it dry! When you wipe off the dry haze you will see a clean, shiny and U/V protected painted surface! No water, power tools to set up or mess – you can use it anywhere, including in hangars and on ramps. Nuvite's NuPol can beat the toughest paint appearance problems, and when used with other Nuvite paint care products, gives you the easiest and best paint care system at the same time!

Core Benefits.

- Heavy-duty 'drywash' cleaning
- Restores shine and colour on oxidized paint on all vehicles
- Easy "wipe on, let dry, wipe off" application procedure.
- Safe to all paints (not for clear-coats)
- Restores a beautiful gloss appearance with an effective UV protectant coating on both painted and metal surfaces
- Easy application in all climates
- Preserves and protects the substrate from further oxidation and intensifies colour on oxidised paint surfaces
- Offers superior cleaning results and protection with fewer man-hours

Directions for use.

For Normal or Lightly Soiled Surface Conditions:

Apply NuPol "as is" by hand with a soft wiping cloth, applicator pad/mop or working quickly and lightly with slow speed orbital buffer to small areas at a time. Agitate area evenly with wet material. Allow to fully dry (usually no more than 5-10 minutes even in the highest humidity conditions). Remove by polishing off with clean mop head or dry wiping cloth to reveal shine.

For Heavily Soiled Surface Conditions:

For the heavy grease, oil, and hydraulic oil build-ups, it is sometimes helpful that the area be wiped down or degreased with Nuvite CitriCut or SS-93 degreasing cleaners prior to the use of NuPol to allow the product to work without serious contamination, then proceed as above.

Safety & storage.

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet (SDS). Only for professional users/specialists. Store in original closed containers away from extremes of temperature.

Frasers Aerospace, 1 St James Road, Brentwood, Essex, CM14 4LH

Tel: +4420 8597 8781 Email:contact@frasersaerospace.com Web:www.frasersaerospace.com