

# PG777

## PREMIUM AIRCRAFT MASKING TAPE

### DESCRIPTION

A pressure-sensitive masking tape designed primarily for the aircraft industry where resistance to strong solvent / high solids polyurethane-based paints is a necessity. Adhesive is specially formulated to provide excellent adhesion to, and transfer free removal from, a variety of prepared aluminum surfaces.

Product is able to support large kraft aprons. It will perform in cycle-bake applications of 140°F for 4-6 hours for up to three cycles. Conformable, extra-strong smooth crepe paper backing provides clean paint break lines and strength for pulling long paint lines with clean, tear-free removal. The release coating is also designed to resist paint flaking upon removal. Not recommended for outdoor use.

### PRODUCT APPLICATION

Paint masking, either OEM or repair. Allows clean removal from aluminum, primed aluminum, and painted aluminum surfaces even when cycled three or more times.

### GOVERNMENT COMPLIANCE

BAC 5034-4



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 9/13

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Smooth Crepe Paper
<b>Adhesive</b>	Natural Rubber/Resin
<b>Adhesion to Steel</b> (oz/in of width) PSTC-101	30 (8.2 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) PSTC-131	30 (131.3 N/25mm)
<b>Elongation</b> (% at break) PSTC-131	12
<b>Total Thickness</b> (mils) PSTC-133	7.7 (0.196mm)
<b>Quick Stick</b> (oz/in of width) PSTC-5	7 (1.9 N/25mm)
To Kraft	17 (4.7 N/25mm)
To Steel	
<b>Color</b>	Beige

