

The **IK FOAM Pro 2+ professional sprayer** has been manufactured for the generation of dry, dense and durable foam. Designed to be used with chemical agents with surfactant properties for applications in professional cleaning, sanitation and disinfection, HVAC system cleaning, vehicle washing and detailing, as well as for the disinfection of food processing areas and industrial kitchens. With the use of the foam we manage to increase the time of contact between the chemical and the surface to clean, cleaning of fabrics and upholstery avoiding the excessive soaking that generates the appearance of fungi and bacteria, and finally to have a greater visual control of the pulverized surface.

The sprayer is equipped with three mixers (orange, grey and green) which allow to vary the type of foam by choosing between wet, intermediate or dry foam.

Connector for compressed air included which allows to be pressurized by means of a compressor in addition to manually.



Perfect for applying cleaning products onto aircraft fuselage surfaces. Reduced run off onto hanger floors and increases dwell time which improves the product effectiveness.

Functional information




Safety valve with depressurisation option



Protective sleeve for valve chamber




Large opening easy filling



Translucent tank with level indicator



Base for greater stability



Safety lock



Ability to identify content via coloured caps



Compressed air plug



3 TYPES OF FOAM



DRY FOAM



INTERMEDIATE FOAM



WET FOAM

Technical information

Technical information	FOAM Pro 2 +
VALVE	Tared at 3 bar / 43.5 psi despressurizable
STANDARD NOZZLES	Special nozzle with fan-type foam
USEFUL CAPACITY	1.25 L - 42 Oz.
TOTAL CAPACITY	1.9 L - 64 Oz.
GROSS WEIGHT	0.7 kg - 1.54 lbs.
NET WEIGHT	0.56 kg - 1.23 lbs.

Logistics data

Logistics data	FOAM Pro 2 +
CODE	8.16.78
EAN	84.14685.10218.8
CONDITIONING	6 units
UNITS PER PALLET	90 units
DIMENSIONS PER PALLET	1200 x 800 x 1070