

LOTOXANE HD



Part Number: CO4820XAM

Pack: 20 Liter

Approvals: Boeing BSS7432 (Previously D6-17487)

HS Commodity Code: X

Product Description.

LOTOXANE HD is a high quality solvent degreaser that offers professional users a versatile, safe alternative to more hazardous products. It incorporates enhanced degreasing power for the removal of heavier deposits.

Typical Applications:

- Removal of oils, greases, flux residues, machining fluids and general contamination in manufacturing process
- Pre cleaning prior to NDT or inspection
- Removal of temporary protective coatings/dewaxing; Cleaning prior to painting or bonding operations
- Degreasing of machinery, components and assemblies during maintenance and repair
- Cleaning electrical and electronic equipment
- De-watering components and electrical systems

Core Benefits.

- Very low odour
- Reduced hazard to user
- Reduces VOCs'
- Can be recycled for reduced consumption
- Non-flammable

Directions for use.

Manual Cleaning: Apply to the surface by spray or paintbrush. Agitate stubborn deposits if required with a stiff brush or pad and wipe away residues with a clean cloth. Suitable for use with most types of degreasing stations.

Dip tank: Allow adequate contact time, typically 10 - 15 minutes, then remove and allow to drain, agitate components if required. To reduce losses from the tank it is advised that a close fitting lid is used. For enhanced performance Lotoxane HD can be heated up to 40°C.

Parts washers: Leave components to air dry naturally.

Ultrasonic tank: Use same method as for dip tank, setting a frequency of 25 kHz.

Note: Drying times can be improved by wiping away excess, forced air or heating up to a maximum of 40°C

Safety & storage.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Provide adequate ventilation. Wear protective clothing, gloves, eye and face protection. Avoid contact with skin, eyes and clothing. Avoid breathing vapours. Avoid release to the environment. Avoid contact with contaminated tools and objects. Do not empty into drains. Do not reuse empty containers. Do not use in paint spraying equipment. Do not eat, drink or smoke when using this product. Wash skin thoroughly after handling. Store at temperatures between 4°C and 40°C. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not store near heat sources or expose to high temperatures.